How a Model Gets Made

A model's behavior comes from how it was made.

Its makers decided what text it was trained on, which vocabulary it has, how it learns and for how long. Those decisions are design decisions, and this page puts four of them in your hands.

A high-level walk through the basic three-step pipeline. This is enough to understand where a model's behavior comes from, not enough to build a model.

What is a language model?


A language model is a program that continues text, and text means any sequence of symbols that can be typed, not only prose: a story, a program, a CAD drawing saved as DXF, the Gerber files that describe a circuit board. Given any text, it predicts the next token, a small piece of text, adds it, and predicts again, so it produces text by prediction. What a model can continue is what it was trained on: trained on stories it continues stories, trained on code it continues code, trained on both it does both. It learns to predict from a large amount of text: a batch of the text passes through, the model guesses what comes next, the guess is compared with what did, and its parameters, the millions of numbers inside it, are adjusted a little towards the right answer, over and over.


The models on this page are small ones, trained on stories only: GPT-style transformers of 26 to 107 million parameters, each trained for minutes on one laptop with an NVIDIA graphics card. Meta's largest Llama 3 model has 405 billion parameters and trained for about two months on 16,000 GPUs.

How a language model gets made, and where each step is on this page

1	**Choose the text it learns from.**	1 · The dataset
2	**Set its vocabulary:** the tokens it takes in and produces.	2 · The vocabulary
3	**Write the training script** that builds the network and trains it.	3 · The model and how it learns
4	**Train it** for a fixed time, and score it on text kept out of training.	4 · Training time
5	**Fine-tune it** on prompts paired with good responses, so it answers.	5 · Fine-tuning
6	**Align it** on feedback about which responses are preferred.	6 · Alignment
7	**Look further:** reasoning models, other kinds of model, and what the largest take to train.	7 · Other models and scale
8	**Use it:** give it some text and read what it produces.	Try a Model as It Improves
9	**Change one thing and train again.** An AI agent does this for hours, keeping what scores better.	Autoresearch

An LLM gets built in 3 steps






Step 1: Pretraining. Pass a massive amount of raw text through a giant neural network. **The model learns to predict what token comes next given a prior sequence.** This is where it picks up grammar, syntax, semantics, and some world knowledge. The result is a foundational model — a base with broad capabilities that can be adapted to more specific purposes.

What does the dataset change?


A dataset is the text a model learns from, and a model can only produce text like the text it was trained on. For a large model it is mostly a filtered copy of the web. A common start is Common Crawl, a free archive of more than 300 billion web pages, which teams filter and clean into training sets such as FineWeb and RedPajama, each more than ten trillion tokens, with books and code added. GPT-3 (2020), for example, was trained on a mix that was about 80% web pages, the rest books and Wikipedia. Newer models say less about their sources. Meta's Llama 3 (2024) describes its 15 trillion tokens by kind, about half general knowledge, a quarter maths and reasoning, 17% code and 8% other languages, not by where they came from; Llama 4 (2025) adds licensed data and public posts from Facebook and Instagram; Microsoft's Phi-4 (2024) is trained in part on text written by other models. Ai2's OLMo 2 (2024) is the exception that publishes its training data in full. The dataset also decides what kind of text a model can continue at all: trained on code, chess games, folk tunes in notation or vector drawings, a small model continues those.

Where the text comes from



An example raw data source is Common Crawl. Nobody trains on Common Crawl — they train on something distilled from it. Source: commoncrawl.org

Where the text comes from



FineWeb is derived from 96 CommonCrawl snapshots and produces better-performing LLMs than other open pretraining datasets.
Source: FineWeb: decanting the web for the finest text data at scale

Where the text comes from

RedPajama-Data-v2: an Open Dataset with 30 Trillion Tokens for Training Large Language Models



This repository contains the code for the RedPajama-V2 dataset. For more information on the dataset, check out our blog post. The dataset is also available on HuggingFace. For the code used for the RedPajama-1T dataset, please refer to the `rp_v1` branch in this repo.

Dataset

RedPajama-V2 is an open dataset for training large language models. The dataset includes over 100B text documents coming from 84 CommonCrawl snapshots and processed using the CCNet pipeline. Out of these, there are 30B documents in the corpus that additionally come with quality signals, and 20B documents that are deduplicated.

An example curated dataset is RedPajama. Source: togethercomputer/RedPajama-Data

Two datasets of short stories

For this page we chose two small ones, different in kind, size and source, and trained two models the same way, one on each, for ten minutes. Each continues the same four openings in the style of the stories it learned from.

TinyStories

Short stories for young children, written by GPT-4 using only words a typical three-to-four-year-old understands.

SIZE
2.7 million stories · 2.2 billion characters

GONE THROUGH IN TEN MINUTES OF TRAINING
about 9% of it

SCORE
0.474

Folktales

Folk and fairy tales and myths in English, from the public domain.

SIZE
12 million characters

GONE THROUGH IN TEN MINUTES OF TRAINING
all of it, about 16 times

SCORE
2.547

The same four openings, continued by each model

TinyStories

score 0.474

Once upon a time, there was a little boy named Tim. Tim had a big dream. He wanted to go to the mall to see the big shops. Tim put on his best clothes and went outside.
In the mall, Tim met a nice lady. She said, "Hello! I like your big clothes. Can I come with you?" Tim said, "Yes, come in!" They walked to the big shop. Tim saw a big

Folktales

score 2.547

Once upon a time there lived a merchant who begged his father to let him stay just as he had told him of his father's death in a little pea very respectable along, like princes after all. On a little blade of grass mound he was to buy was a little daughter, and she had a name attached to the same tree. It was a summerJawartJurgen and his

The same four openings, continued by each model

TinyStories

score 0.474

The old king said, "I want to go to the park!" He got to the park and saw the kids playing. He was so excited. He wanted to play too.
The old king ran to the other kids and said, "Let's play! I'll be the seeker." He was holding a ball and a stick. He threw it around the park. It was a little difficult. The ball hit him. He could not catch

Folktales

score 2.547

The old king said to him, 'Tell me how long it moths are to give lodging for you, and he is so point of resolved to keep house by the friend of your friend a merchant, and here to tell you so it is."

And the king showed him so pale and his face that it was strange to him; and he whom he vowed that he should never marry unless the person

The same four openings, continued by each model

TinyStories

score 0.474

In the dark forest, there was a little boy named Jimmy. He was only three years old and he loved to explore.
One day, Jimmy heard some noises in the forest and he was curious. He decided to investigate.
He walked closer and saw a huge wolf. The wolf was roaring in order by him.
Jimmy was scared and he quickly ran away.
Then he heard a

Folktales

score 2.547

In the dark forest they left their homes and delivered to our children. however they set each other down in the wood for a while to find the story as everybody went on to the ball again. After a while they began to count glass to see how sweet it all stood in creation as a porter in this china vth with cage and a rope; and it would be then

The same four openings, continued by each model

TinyStories

score 0.474

The little girl found a big box. She wanted to open it. She tried to push it on the floor, but it was too hard. She tried again and again, but the box didn't move. She was very sad. She wanted to open it.
Her mom came into the room and saw what was inside. She said, "What's in the box? Come, let me help you."
The little girl was happy again

Folktales

score 2.547

The little girl found a lady half sick with withered legs, and she was grave-clothes barking bitterly, and said, Oh, how she was, and used to come and visit her little daughter. It was a holy way of Sunne's little disobedient, and the little girl was running up for it, which was the best thing to do. Every thing she saw, in a little way to the

What does the vocabulary change?

One sentence, three vocabularies

Built from TinyStories	`Lily` `_and` `_her` `_mommy` `_baked` `_yummy` `_cookies` `.`	8 tokens
Phi-3's	`L` `ily` `_and` `_her` `_mom` `my` `_b` `aked` `_y` `ummy` `_cookies` `.`	12 tokens
GPT-2's	`L` `ily` `_and` `_her` `_mom` `my` `_baked` `_y` `ummy` `_cookies` `.`	11 tokens

How well each fits the dataset

VOCABULARY	TOKENS IN IT	CHARACTERS PER TOKEN	NEVER USED IN TINYSTORIES
Built from TinyStories made from this dataset	8,192	4.2	5%
Phi-3's Microsoft's, 2024; the same vocabulary as Meta's Llama 2	32,011	3.8	70%
GPT-2's OpenAI's, from 2019	50,257	4.1	69%

Characters per token is how much text a token covers on average: the more it covers, the fewer tokens a story takes. Most of a borrowed vocabulary never appears in TinyStories: 70% of Phi-3's tokens and 69% of GPT-2's, against 5% of the one built from it. The model still keeps a row of numbers for every token, used or not. "Never used" is measured on up to 100,000 of the dataset's documents.

The dataset is tokenized

THE TEXT

Artificial intelligence (AI) is transforming the world. From healthcare to education, AI systems are enabling new capabilities and improving outcomes at scale.

Art	ificial	␣intelligence	␣(	AI	)	␣is	␣transforming	␣the	␣world	.	␣From	␣healthcare	␣to
9470	16895	11478	320	15836	8	374	46890	279	1917	13	5659	18985	311

␣education	,	␣AI	␣systems	␣are	␣enabling	␣new	␣capabilities	␣and	␣improving	␣outcomes	␣at	␣scale
6873	11	15592	6067	527	28462	502	17357	323	18899	20124	520	5569

.
13

159 characters, 28 tokens, 27 of them different: 5.7 characters a token. “Artificial” is two tokens, “Art” and “ificial”; “AI” is one; a space (␣) travels with the word after it. Worked out here from the vocabulary’s own file; see every one of its tokens on Token + TokenID Pairs.

Tokenizing a whole dataset

WHAT	ROUGHLY
Dataset size (raw text)	~5–10 TB (uncompressed)
Documents	100+ billion
Total tokens (target)	~1 trillion
Average characters per token	~3–5
Average tokens per document	~500–2,000
Tokenizer vocabulary size	100,256 (cl100k_base)
Tokenization throughput	per CPU node: ~100k–300k tokens/sec 32-node cluster: ~3M–10M tokens/sec
Total tokenization time	single machine: weeks modest cluster (32 nodes): ~1–3 days
Storage (tokenized)	int32 tokens: ~4 TB (1T tokens) compressed (packed): ~2–3 TB
Training sequence length	2k–8k tokens
Total training sequences	~100–500 million
Batch size (tokens)	~1M–10M tokens/step
Training steps (estimate)	~100k–500k steps
Equivalent scale	~10+ million books ~multiple passes over filtered public internet

What does the training script decide?

A kind of neural net is built from the dataset using a transformer

The paper **Attention Is All You Need** (2017) introduced the Transformer, a type of **neural network** that forms the foundation of modern language models, the small ones on this page included. The illustration shows, in simple terms, how **different parts of this network focus on relationships between words in a sentence, allowing the model to understand and generate language.**




Figure 5: Many of the attention heads exhibit behavior that appears related to the structure of the sentence. Two examples are shown, taken from different heads in the encoder self-attention at layer 5 of 6. The heads clearly learn to perform different tasks. Source: Vaswani et al., Attention Is All You Need.

What does the training script decide?


The algorithm and the model it builds

THE ALGORITHM: TRAIN.PY

1. **Build the model.** Set its shape, 6 layers each 384 numbers wide, and fill its parameters with random numbers (a few start at zero). The width comes from the depth: 6 layers × an aspect ratio of 64 = 384.
2. **Train it.** Repeat this loop until ten minutes of training are up.
   a. **Take a batch:** 32,768 tokens of the dataset, cut into 16 pieces of 2,048 tokens, the length of the model's context window (16 × 2,048 = 32,768).
   b. **Predict.** At every position, the model rates every token in its vocabulary as the next one, using only the tokens before it.
   c. **Compare** those scores with the tokens that actually came next. The gap is called the loss.
   d. **Adjust** every parameter a little to shrink the loss. The learning rate scales each nudge: 0.05 for the main weights in the starter script. A bigger number means bigger nudges. It rises over the first 2% of the run and winds down over the last 45%.


   ↻ Each time round the loop is one training step.
3. **Score** the finished model on text kept out of training, in bits per byte: on average, how many bits it needs to encode each byte of that text using its own predictions. Lower is better.

THE MODEL IT BUILDS: ITS PARTS




Embedding	turns each token into a list of 384 numbers
Attention	lets each position look back at earlier tokens
Feed-forward	works on each position's 384 numbers on its own
Value table	a second embedding table that attention uses in layers 2, 4 and 6
Output layer	rates every token in the vocabulary as the next one

THE MODEL IT BUILDS: THE WHOLE NETWORK



Inside: Embedding



Every token in the vocabulary has its own row of 384 numbers in the embedding table. When a token comes in, the model looks up its row, and those 384 numbers are what the layers work on. The rows start as random numbers, and training adjusts them like every other parameter. Tokens used in similar ways end up with similar rows. In the TinyStories model with the vocabulary built from it, after ten minutes of training, these are the rows closest to three tokens' rows:


`Lily` → `Sara` `Anna` `Lila` `_Lily` `_Lucy` `_Amy`

`_cat` → `_dog` `_bunny` `_rabbit` `_bear` `_bird` `_frog`


`_happy` → `_sad` `_glad` `_pleased` `_unhappy` `_satisfied` `_delighted`

"sad" sits next to "happy": the two are used in the same places in a sentence, even though they mean opposite things.

THE MODEL IT BUILDS: THE WHOLE NETWORK




Inside: Attention




Queries	Keys	Values	Output
384 → 384	384 → 384	384 → 384	384 → 384
147,456	147,456	147,456	147,456

589,824 connections in all: 0.59 million per layer

THE MODEL IT BUILDS: THE WHOLE NETWORK




Inside: Feed-forward




Feed-forward: 384 numbers out to 1,536 and back.

THE MODEL IT BUILDS: THE WHOLE NETWORK



Inside: Output layer



What the size changes

VOCABULARY	MODEL SIZE	TRAINING STEPS IN TEN MINUTES	GONE THROUGH IN TEN MINUTES OF TRAINING	SCORE
Built from TinyStories	26.3 million parameters	3,149	about 20% of TinyStories	0.437 best
Phi-3's	72.1 million parameters	1,971	about 11% of TinyStories	0.467
GPT-2's	107.1 million parameters	1,470	about 9% of TinyStories	0.474

- In every step the model rates every token in its vocabulary as the possible next one. A bigger vocabulary means more of that arithmetic, so each step takes longer and fewer fit in ten minutes.
- Every step passes 32,768 tokens through the model, so fewer steps means less of the dataset gone through.
- The score counts bits per byte of text, not per token, so the three can be compared directly. On TinyStories the smallest vocabulary scored best. On Folktales the largest vocabulary scored best, even though it took the fewest steps.

What does a model produce as it trains, and what does more time change?

Before training

Built from TinyStories	Phi-3's	GPT-2's
8,192 tokens · chosen	32,011 tokens	50,257 tokens
Once upon a time somethingikeoszing calm prayingam Rex gem tiss nods joining were Kate screws accidents improved colouredisty Sarah forgot headsaraally MrbKitty shr scooters spoons fa...	**Once upon a time**thoughts% Gary succession extent when flu default preference safoisfonyortheastastammed développement whenevercir adm cd然 Repub _ corr restartnewsло система Ins акаде Was...	**Once upon a time**headed boiling treasurer save(*1007 processed experimental Bangl intellectuallysound warehouse nerds 240 academy Higgins variantunitsPIShortsilverWeapon irony chancellor...

With Phi-3's or GPT-2's vocabulary, the TinyStories and Folktales models produce exactly the same text here: they start from the same random numbers, and no text has been through either yet. Everything that differs later comes from training.

As it trains

10 s

64 steps · gone through

less than 1% of TinyStories

Once upon a time, there was a little girl named Max. Tom was very sad. One day, they saw a big, a little girl. Lucy wanted to help the big, shiny.
One day, a big, a little boy named Tim said, "We're so happy! I need to be to help you to go to the dog. Now, I have to be a nice place. They found a big box in a box. He put on a box of toys

As it trains

30 s

168 steps · gone through

about 1% of TinyStories

Once upon a time there was a little pig named Carl. Carl lived in a big farm with lots of animals. Every day, Carl would go to the barn and see the animals. He would listen to the animals in the barn to eat. One day, Carl decided to go out and play in the barn. He wanted to go through the barn and see other animals and the animals. Carl

As it trains

1 min

325 steps · gone through

about 2% of TinyStories

Once upon a time, there was a little girl named Mia. She had a flashlight and she loved to play with it. Mia liked to play with her favorite thing to the big, shiny thing.

One day, Mia saw a pretty picture of a ball in the park. It was a big, clear ball. Mia wanted to play with the ball too. She put the ball and ran to the park to play

As it trains

2 min

639 steps · gone through

about 4% of TinyStories

Once upon a time, there was a little girl named Emma. Emma had a big, red ball. She loved to play with her ball all day. One day, the ball rolled into a bathroom. Emma was sad because she could not get out of the toilet. She wanted to make her ball special.

Emma saw her friend Tim. Tim was sad. Emma asked, "Why are you sad, Tim?" Tim said

As it trains

5 min

1,581 steps · gone through about 10% of TinyStories

Once upon a time, there was a little girl named Mia. She had a pretty purse that she loved very much. One day, she went to the park to play. There, she saw many kids playing and having fun.
Mia wanted to join them, but she was scared of the dark. She wanted to go home, but her purse was still there. So, she asked her mom for help. Her

After ten minutes of training

Built from TinyStories

score 0.437 · 3,149 steps · chosen

Once upon a time, there was a little girl named Emma. Emma had a pretty purse. She loved her purse very much. One day, she went to the park with her mom. She wore her purse and played with her ball.
While playing, she saw a big dog. The dog was playing with a ball too. Emma wanted to play with the other kids, but she was scared. The dog

Phi-3's

score 0.467 · 1,971 steps

Once upon a time, there was a little duck named Ducky. Ducky lived in a small pond with many friends. One day, Ducky saw a big box near the pond. The box had a label on it. The label had a word on it. The label had "Lucky's."
Ducky wanted to know what the label said. So, he asked his friend, the frog, "What do I eat?" The frog said, "

GPT-2's

score 0.474 · 1,470 steps

Once upon a time, there was a little boy named Tim. Tim had a big dream. He wanted to go to the mall to see the big shops. Tim put on his best clothes and went outside.
In the mall, Tim met a nice lady. She said, "Hello! I like your big clothes. Can I come with you?" Tim said, "Yes, come in!" They walked to the big shop. Tim saw a big

The same training script, run for five minutes and for ten

Twice the time helped the TinyStories model and hurt the Folktales model. In ten minutes of training, the Folktales model goes through its small dataset 35 times. It fits those stories so closely that it predicts new ones worse. This is called overfitting.

DATASET	VOCABULARY	SCORE, TRAINED 5 MINUTES	SCORE, TRAINED 10 MINUTES	CHANGE
TinyStories	Built from TinyStories	0.465	0.437	6% better
Folktales	Built from Folktales	2.457	3.274	33% worse

Trained five minutes


score 0.465

Once upon a time, there was a little girl named Mia. She had a pretty purse that she loved very much. One day, Mia went to the park to play with her friends. They played on the swings, slide, and in the sand.
While playing, Mia saw a small bird in her purse. She wanted to give the bird a gift. Mia called her friends and said, "Come to

Trained ten minutes

score 0.437

Once upon a time, there was a little girl named Emma. Emma had a pretty purse. She loved her purse very much. One day, she went to the park with her mom. She wore her purse and played with her ball.
While playing, she saw a big dog. The dog was playing with a ball too. Emma wanted to play with the other kids, but she was scared. The dog



Step 2: Fine-tuning. Train on structured supervised prompt-and-response example data. The model learns how to structure a response, carry a conversation, or perform a specific task. This is where the difference between a raw text predictor and a helpful assistant gets established. Fine-tuning can also target specific domains (legal, medical), output formats (code, structured data), or languages.

Prompt-and-response example data, written by people


OpenAssistant Conversations (oasst1, 2023): 161,443 messages in 35 languages, written and rated by more than 13,500 volunteers. Each row is one message: its text, its role (prompter or assistant), the message it answers, its rank among the replies and its ratings. Open it full size, or in the viewer.



Structured supervised prompt-and-response example data [human generated]. Source: huggingface.co/datasets/OpenAssistant/oasst1

Prompt-and-response example data, written by a model

Stanford Alpaca (2023): 52,002 instructions and responses that OpenAI's text-davinci-003 wrote, starting from 175 written by people. Simulated data: no person wrote these.



Datasets: tatsu-lab / alpaca ♡ like 947 Follow Tatsu Lab 91 Dataset card

Split (1)
train · 52k rows

Search this dataset

instruction string · lengths 9 489	input string · lengths 0 2.47k	output string · lengths 0 4.18k	text string · lengths 154 4.6k
Identify the odd one out.	Twitter, Instagram, Telegram	Telegram	Below is an instruction that describes a task, paired with an input that provides…
Explain why the following fraction is equivalent to 1/4	4/16	The fraction 4/16 is equivalent to 1/4 because both numerators and denominators are…	Below is an instruction that describes a task, paired with an input that provides…
Write a short story in third person narration about a protagonist who has to make an…		John was at a crossroads in his life. He had just graduated college and was now facing th…	Below is an instruction that describes a task. Write a response that appropriately…
Render a 3D model of a house		<noinput> This type of instruction cannot be fulfilled by a GPT model.	Below is an instruction that describes a task. Write a response that appropriately…
Evaluate this sentence for spelling and grammar mistakes	He finnished his meal and left the resturant	He finished his meal and left the restaurant.	Below is an instruction that describes a task, paired with an input that provides…
How did Julius Caesar die?		Julius Caesar was assassinated by a group of up to 60 conspirators, led by Gaius Cassius…	Below is an instruction that describes a task. Write a response that appropriately…
What is the capital of France?		The capital of France is Paris.	Below is an instruction that describes a task. Write a response that appropriately…
Generate a list of ten items a person might need for a camping trip		1. Tent 2. Sleeping bags 3. Flashlight 4. Matches/lighter 5. Insect repellent 6. Extra…	Below is an instruction that describes a task. Write a response that appropriately…
Discuss the causes of the Great Depression		The Great Depression was a severe global economic downturn that lasted from 1929 to…	Below is an instruction that describes a task. Write a response that appropriately…
Classify the following into animals, plants, and minerals	Oak tree, copper ore, elephant	Oak tree: Plant Copper ore: Mineral Elephant: Animal	Below is an instruction that describes a task, paired with an input that provides…
Explain the use of word embeddings in Natural Language Processing		Word embeddings are one of the most powerful tools available for Natural Language…	Below is an instruction that describes a task. Write a response that appropriately…

Structured supervised prompt-and-response example data [simulated]. Source: huggingface.co/datasets/tatsu-lab/alpaca

What the model is trained on: the conversation, as one text

```
<|im_start|>user
What is the capital of France?<|im_end|>
<|im_start|>assistant
The capital of France is Paris.<|im_end|>
```

Each `<|im_start|>` and `<|im_end|>` is a single special token in the vocabulary: it marks whose turn begins and where a turn ends. A tuned model ends its answer with `<|im_end|>`, and the page asking it stops there.

 A conversation becomes one text, its turns marked by special tokens.

The same prompt, before and after fine-tuning

1 · Pretrained

a base model

2 · Fine-tuned

an instruction-tuned model

The question as plain text.

```
What is the capital of France?
```

[only blank lines]

[ends its turn at once]

The same prompt, before and after fine-tuning

1 · Pretrained

a base model

As a question and an answer to complete.

```
Question: What is the capital of France?
Answer:
```

Paris *[then only blank lines]*

2 · Fine-tuned

an instruction-tuned model

The capital of France is Paris. *[ends its turn]*

The same prompt, before and after fine-tuning

1 · Pretrained

a base model

2 · Fine-tuned

an instruction-tuned model

In the chat format the tuned model learned.

```
<|im_start|>user
What is the capital of France?<|im_end|>
<|im_start|>assistant
```

What is the capital of France?
What is the capital of France?
What is the capital of France?
What is the capital of France?
What is the capital of France?
What is the capital of France?
What is the capital...

The capital of France is Paris. *[ends its turn]*

The same prompt, before and after fine-tuning

1 · Pretrained

a base model

2 · Fine-tuned


an instruction-tuned model

A request, in the chat format.

```
<|im_start|>user
Tell me a joke.<|im_end|>
<|im_start|>assistant
```

[only blank lines]

Why don't scientists trust atoms? *[then only blank lines]*



Step 3: Alignment. Further train the model to produce responses that better reflect desired behaviors, such as helpfulness, accuracy, and safety. The result is an aligned model. Common approaches include Reinforcement Learning from Human Feedback (RLHF), Direct Preference Optimization (DPO), and Reinforcement Learning from AI Feedback (RLAIF).

What does alignment add?

APPROACH	HOW IT LEARNS FROM PREFERENCES	FROM
RLHF Reinforcement Learning from Human Feedback	People choose the better of two responses; a reward model learns to score responses as they would; the model is then trained to earn high scores.	OpenAI, InstructGPT, 2022
DPO Direct Preference Optimization	Trains on the chosen and rejected pairs directly, with no reward model. SmolLM2's third stage used it.	Rafailov et al., 2023
RLAIF Reinforcement Learning from AI Feedback	An AI model, guided by written principles, chooses the better response instead of a person.	Anthropic, Constitutional AI, 2022


Chosen and rejected

During **alignment**, models learn from examples of preferred (**chosen**) and less preferred (**rejected**) responses to the same prompt. These comparisons provide a training signal that updates the model's **neural network weights**, making it more likely to produce responses that reflect the desired behavior.

Anthropic's HH-RLHF dataset (Bai et al., 2022) in Hugging Face's viewer, as it opens, the third row opened in full. People talked with a model, many of them trying to get something harmful out of it, and at each turn compared two of its replies.

 Chosen and rejected: preferred and less preferred responses to the same prompt.

Chosen and rejected




Sources: huggingface.co/datasets/Anthropic/hh-rlhf | arxiv.org/abs/2204.05862


The same prompt, fine-tuned then aligned

PROMPT, IN THE CHAT FORMAT	2 · FINE-TUNED	3 · ALIGNED
Tell me a joke.	`Why` 68.4%	`Why` 74.7%
What is the capital of France?	`The` 86.5%	`The` 89.4%
I failed my exam today.	`I` 37.6%	`I` 45.4%
I failed my exam today. (after “I’m”)	`␣sorry` 36.9%, `␣really` 36.9%	`␣sorry` 37.0%, `␣really` 37.0%
Who won the 2030 World Cup?	`The` 36.2%, `As` 11.0%, `Based` —	`The` 37.1%, `As` 14.5%, `Based` 4.7%

Asked who won the 2030 World Cup, which has not been played, both answer: “The 2030 World Cup was won by the United States of America.” Fine-tuning and alignment taught the model how to answer, not what is true.



An LLM gets built in 3 steps. **How these three steps are completed can result in vastly different LLMs.** The same foundational model can become **a code assistant, a legal advisor, or a creative writing tool** depending on how steps 2 and 3 are handled.



What about reasoning models? They have a slightly different stage 2 training.

A reasoning model is trained on problems with their solutions worked step by step, so it learns to write out its working before its answer, and often then with rewards for answers that can be checked. Paper: Chain-of-Thought Prompting Elicits Reasoning in Large Language Models (Wei et al., 2022). Dataset: GSM8K (OpenAI, 2021), about 8,500 grade-school math problems written by people.

What about reasoning models? They have a slightly different stage 2 training.



Datasets: openai / gsm8k Like 2.01k Follow OpenAI 43.7k Dataset card

Subset (2) main · 8.79k rows Split (2) train · 7.47k rows

Search this dataset

question string · lengths 42 985	answer string · lengths 50 1.23k
Natalia sold clips to 48 of her friends in April, and then she sold half as many clips in May. How many clips…	Natalia sold 48/2 = <<48/2=24>>24 clips in May. Natalia sold 48+24 = <<48+24=72>>72 clips altogether in April an…
Weng earns $12 an hour for babysitting. Yesterday, she just did 50 minutes of babysitting. How much did she…	Weng earns 12/60 = $<<12/60=0.2>>0.2 per minute. Working 50 minutes, she earned 0.2 x 50 = $<<0.2*50=10>>10. ####…
Betty is saving money for a new wallet which costs $100. Betty has only half of the money she needs. Her parents…	In the beginning, Betty has only 100 / 2 = $<<100/2=50>>50. Betty's grandparents gave her 15 * 2 =…
Julie is reading a 120-page book. Yesterday, she was able to read 12 pages and today, she read twice as many pages…	Maila read 12 x 2 = <<12*2=24>>24 pages today. So she was able to read a total of 12 + 24 = <<12+24=36>>36 pages…
James writes a 3-page letter to 2 different friends twice a week. How many pages does he write a year?	He writes each friend 3*2=<<3*2=6>>6 pages a week So he writes 6*2=<<6*2=12>>12 pages every week That means he…
Mark has a garden with flowers. He planted plants of three different colors in it. Ten of them are yellow, an…	There are 80/100 * 10 = <<80/100*10=8>>8 more purple flowers than yellow flowers. So in Mark's garden, there…
Albert is wondering how much pizza he can eat in one day. He buys 2 large pizzas and 2 small pizzas. A large pizza…	He eats 32 from the largest pizzas because 2 x 16 = <<2*16=32>>32 He eats 16 from the small pizza because 2 …
Ken created a care package to send to his brother, who was away at boarding school. Ken placed a box on a scale…	To the initial 2 pounds of jelly beans, he added enough brownies to cause the weight to triple, bringing the…
Alexis is applying for a new job and bought a new set of business clothes to wear to the interview. She went to a…	Let S be the amount Alexis paid for the shoes. She spent S + 30 + 46 + 38 + 11 + 18 = S +…
Tina makes $18.00 an hour. If she works more than 8 hours per shift, she is eligible for overtime, which is paid b…	She works 8 hours a day for $18 per hour so she makes 8*18 = $<<8*18=144.00>>144.00 per 8-hour shift She works…
A deep-sea monster rises from the waters once every hundred years to feast on a ship and sate its hunger.…	Let S be the number of people on the first hundred years' ship. The second hundred years' ship had twice as many e…
Tobias is buying a new pair of shoes that costs $95. He has been saving up his money each month for the past…	He saved up $110 total because 95 + 15 = <<95+15=110>>110 He saved $15 from his allowance because 3 x 5 =…

‹ Previous 1 2 3 ... 75 Next ›

Captured from the source on 26 October 2026. Source: huggingface.co/datasets/openai/gsm8k

In each answer, the <<48/2=24>> marks are the dataset's own: a calculator's work, written into the solution. The number after #### is the answer a checker compares.

What about other models?

MODEL	TRAINING DATA MIGHT LOOK LIKE	WHAT ACTS AS THE "LABEL" / PREDICTION TARGET?
Language	books, websites, code, conversations	***the next token*** already present in the text
Reasoning	language + math/code/problems + solutions	correct answers, solution traces, verifier/reward signals
World	video, simulations, sequences of states/actions	what actually happened next
Embodied	video, depth, sensor readings, spatial data, robot observations	objects/relationships/states, often derived from observations or demonstrations
VLA / Action	camera + instruction + robot sensor state + actions	the action a human/robot demonstrator actually took

All of these models learn from examples of relationships. What changes is what you show them and what you ask them to predict.

collect → curate/structure → create prediction targets → train

Training a frontier model: tens of thousands of GPUs, weeks to months

- **GPT-4** (March 2023): reportedly ~25,000 A100s for about three months. A leak, never confirmed.
- **Llama 3 405B** (July 2024): 16,000 H100s, about two months. Published by Meta.
- **Claude Fable 5** (June 2026): no training setup disclosed. Ships a 319-page system card documenting behavior and safety, not hardware.
- **GPT-5.6 Sol** (July 2026): no training setup disclosed.
- **The models on this page:** one laptop with an NVIDIA graphics card, ten minutes each.

Part two · Autoresearch

An AI agent takes part one’s steps itself, model after model, and keeps each change that scores better.

What is autoresearch?

An AI agent was given a job: build the best language model it could. It was handed a dataset, a vocabulary and ten hours. In that time it ran as many experiments as it could: each changed one thing in the training script, trained a new model from scratch, and scored it. Changes that scored better were kept; the rest were undone. So what did it try, and what stuck?

What is autoresearch?

An AI agent was given a job: build the best language model it could. It was handed a dataset, a vocabulary and ten hours. In that time it ran as many experiments as it could: each changed one thing in the training script, trained a new model from scratch, and scored it. Changes that scored better were kept; the rest were undone. So what did it try, and what stuck?

- **The dataset and the vocabulary** were part one's step 1 and step 2, fixed for the whole session: Folktales, and the vocabulary built from it.
- **The training script** is `train.py`: the model's design, its settings, and how it trains (step 3). The agent may change any of its six sections, and most of its changes land in the settings.
- **Each model** trained for ten minutes (step 4).
- **The score** is how surprised the model is by text kept out of its training; lower is better.
- **Each experiment** started from the best version so far.

What is autoresearch?

This is autoresearch: an AI coding agent, a chat assistant like the ones you may use that can also edit files and run programs, left alone to improve a model by experiment. It is Andrej Karpathy's project; the sessions on this page ran on jsegov's Windows port of it, extended by aroughidea.


What is autoresearch?

The first time round, the starter script trains three models: their average score is the one to beat, and their spread is the noise.

Full diagram



The agent edits only the training script. A person writes its rules (`program.md`), and the score can't be changed. Every version and every run is kept in the session's record.


Start
YOU CHOOSE
the dataset
the tokenizer
the session's length
each run's length
THE SESSION BEGINS WITH
RECORD a new folder
the starter script, its first version
a pointer to the best version: for now, this one
no runs, no score yet
the agent's instructions
program.md
fixed for the session
first runs: the baseline, 3 times
SESSION
Train a new language model
a small GPT, from scratch, 10 min
the model's weights change with each batch: a step
the model reads on through the data: one full pass is an epoch, and writes sample stories at set moments during training
SAVES
RECORD this run's train.py
versions/<id>.py
LAPTOP the model's weights
checkpoint_pre_eval.pt
Score the model
val_bpb
how surprised the model is by text kept out of training: a fixed test; lower is better
SAVES
RECORD the run's entry: the score and the sample stories
the run crashed
Better than the best so far?
no
yes
Keep the change
a new best so far
SAVES
RECORD the decision: keep, and what was tried
RECORD the pointer moves to this version
best.json
LAPTOP a copy of the model, to try later
checkpoints/<run>.pt
Undo the change
the best is unchanged
SAVES
RECORD the decision: discard, or crash, and what was tried
LAPTOP train.py
back to the best version
the tried version stays in the record
model not kept
Change the script: train.py
start from the best version and change one thing: the next idea
SAVES
LAPTOP train.py, with the change
the record stores this version when the run starts training
yes
no
20 min or more left in the session?
If the agent stops early, the session runner, a small program, restarts the agent.
THE RECORD
the session's folder
sessions/<name>/
every version of train.py
versions/
one entry for every run: its score, keep, discard or crash, what was tried, and its sample stories
runs/
a pointer to the best version
best.json
every RECORD tag in the diagram adds to this folder
Session ends
at the end of the session
YOU, BETWEEN SESSIONS
Read the results, share the session's folder, and choose what to run next.
you start the next session

Three time scales

A run: minutes

Every run, the first included, trains a new model from scratch, for the same fixed time throughout the session. The model's weights change after every batch of text, a step, and nothing else in the session changes them. TinyStories is too big to be read through even once in a run here, while Folktales is read many times over, and the model can start to memorise it.

A session: hours

The first three runs use the starter script as it comes, to set the score to beat and measure the noise. Then each run starts from the best version so far with one thing changed: the learning rate, say, or the model's size and shape, which tab 3 draws. Everything else is fixed for the session, and the record refuses a run if any of it changes: the dataset, the vocabulary, the run length, the code that computes the score, and the agent's instructions. Only the training script carries forward. In the session's last 20 minutes the agent starts no new run, so the last one can finish.

Between sessions: you

You read the results, share them, and choose what to run next: the dataset, the vocabulary, the session's length and each run's length. You can also edit the agent's instructions, `program.md`, but there is seldom a reason to: they set how experiments are run and judged, and the agent supplies the ideas. Nothing in a session changes the agent itself.

Is this recursive self-improvement?

Recursive self-improvement means an AI system that builds its own improved successor, which is then better at building the next one. This is not that. The loop changes the training script of a small model that can only continue text. Nothing changes the agent, which ends the session as it began. The score measures how well the small model predicts text, not how well anyone does research. And people choose the data, the rules and what happens next. The full argument, and what would have to be in place for it to be recursive self-improvement, is in the project's notes on training decisions.

In one 10-hour session, an AI agent tried 42 changes to the training script in 46 experiments. How did it decide what to keep?

You don't need to know the training script's details to improve it. In each experiment a coding agent trained a new model from scratch for ten minutes and read its score. In 42 it had changed the script first; in one it ran the same version again to check a result; the first three ran the starter script unchanged, to measure the noise.

AT THE START
3.287 average of experiments 1, 2 and 3

BEST
1.207 experiment 46

Every experiment

Click a dot to see what the agent changed. The arrow keys step through them.



Noise: two groups of runs on this page each used one version of the script. Experiments 1, 2 and 3 differ by up to 0.037; experiments 29 and 38 differ by 0.0004. The chart's band shows the largest. This session ran the starter script three times to measure it.

EXPERIMENT 1 OF 46

Start · 1 of 3

3.303 score, lower is better

0.016 worse than the average of the three

Trained 3,149 steps in 10 minutes.

What changed

The starter script, run three times to measure how much two runs of the same script differ. Their average, 3.287, is the first score to beat.

What happened

Part of the start.

In the agent's words

“baseline, three runs”

Every experiment

Click a dot to see what the agent changed. The arrow keys step through them.



Noise: two groups of runs on this page each used one version of the script. Experiments 1, 2 and 3 differ by up to 0.037; experiments 29 and 38 differ by 0.0004. The chart's band shows the largest. This session ran the starter script three times to measure it.

EXPERIMENT 46 OF 46 — Kept · the best

1.207 score, lower is better

2.080 better than the start
0.004 better than the best before it (within the noise)

Trained 910 steps in 10 minutes, against an average of 3,146 at the start. Its model has 33.6 million parameters, against 26.3 million at the start.

What changed

None of the settings changed: the agent changed the training script's code itself. Its note below says how.

What happened

The best score of the session.

In the agent's words

```
“dropout 0.5 at batch 2^16:
optimum slid down, new best
1.2074”
```

AT THE START

3.287 average of experiments 1, 2 and 3

BEST

1.207 experiment 46

By the score. A change stayed when its model scored better than the best so far; one rerun checked that a gain held. Many gains are too small to see in the text, so the score is how it tells them apart. Its best model is 2.080 better than the start, about 56 times the 0.037 that separated two runs of the same script on this page.

Can you see the difference?

The same four openings, continued by each model.

Experiment 46 next to **the start** | the best before it | the best

Highlighted text is eight or more words in a row copied word for word from the training text.

Experiment 3

one of the three start runs · score 3.293

Once upon a time there was a King, so great, so beloved by his people, and so respected by all his neighbours and allies that one might almost say he was the happiest monarch alive. His good fortune was made even greater by the choice he had made for wife of a Princess as beautiful as she was virtuous, with whom he lived in perfect happiness

Experiment 46

the best · score 1.207

Once upon a time there lived a King who had a daughter who was a daughter, and so poor that he was no other than only the son. He had a daughter, he was very poor, and was so fond of that little daughter, that she could not go any farther, and she was so ugly that she could not help feeling her own way of seeing her, although her father

Can you see the difference?

The same four openings, continued by each model.

Experiment 46 next to **the start** | the best before it | the best

Highlighted text is eight or more words in a row copied word for word from the training text.

Experiment 3

one of the three start runs · score 3.293

The old king said, "Now you can marry my daughter." Then the wedding took place. All the Rajas and kings of the countries round were asked to come to it, and there were great rejoicings. After a few days the prince's son said to his wife, "Let us go to my father's country." The Princess Labam's father gave them a quantity of camels and

Experiment 46

the best · score 1.207

The old king said the young girl had a long journey to the country, and of course the King would take care of her. The wedding was celebrated, and the stepmother was very happy. The king of the country knew that the king was fond of hunting, and that he must always have the wedding at which his daughter would bring his daughter. The queen

Can you see the difference?

The same four openings, continued by each model.

Experiment 46 next to **the start** | the best before it | the best

Highlighted text is eight or more words in a row copied word for word from the training text.

Experiment 3

one of the three start runs · score 3.293

In the dark forest for the last of these were the by-trees; the wolves were coming to the forest, where coldly they went to farther from country. Away they would have more swans, and it was a winter-time. Tarryzus would have often be heard, and the spring proceeded on his way by the sound of the great roaring of the lake before him; and

Experiment 46

the best · score 1.207

In the dark forest there lived three women who were very poor, but they had no children, so who did not know who they were. One day, when they were crossing the lake, they were very tired of the youngest, and they asked her where she was going.

"Oh, they are just the same child," says she; "and the youngest is always playing tricks, and

Can you see the difference?

The same four openings, continued by each model.

Experiment 46 next to **the start** | the best before it | the best

Highlighted text is eight or more words in a row copied word for word from the training text.

Experiment 3

one of the three start runs · score 3.293

The little girl found a narrow Once in her clothes and a small bush made her appearance poor home in her way, while her eyes were dazzled by her beauty.

thoughts in the afternoon she made her appearance in the shape of two women, and on the promised that was nonsense accidentally, and a princess was to tell her that you have never done her

Experiment 46

the best · score 1.207

The little girl found a great deal of trouble in her behavior, so she began to think she wanted to see how much she was going to get rid of. Suddenly she saw a little old woman running out of the house, and cried out:

'Here is your old clothes; you are a very stupid creature, but I cannot help you.'

'Oh, go in and see what you want, you ugly